

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 06/10/2014 Supersedes: 06/10/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form · Mixture

Product name : Amerimix Fiber Base Coat Concentrate Stucco (AMX 755)

65401036 - 3000 lb Product code

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Various.

Details of the supplier of the safety data sheet

Oldcastle Architectural Inc. 900 Ashwood Parkway Suite 600 Atlanta, GA 30338 - USA

T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

Emergency telephone number

: CHEMTREC (800) 424-9300 **Emergency number**

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral) Skin Irritation 2 Serious Eye Damage 1 Skin Sensitization 1 Carcinogenicity 1A

Specific Target Organ Toxicity After Single Exposure 3 Specific Target Organ Toxicity After Repeated Exposure 1

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS05

GHS07

GHS08

Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US)

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards

No additional information available

Unknown acute toxicity (GHS-US)

23 % of the mixture consists of ingredient(s) of unknown acute toxicity.

06/10/2014 EN (English) Page 1

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Cement, portland, chemicals	(CAS No) 65997-15-1	20 - 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Ashes, residues	(CAS No) 68131-74-8	30 - 50	Not classified
Iron oxide (Fe2O3)	(CAS No) 1309-37-1	5 - 10	Not classified
Quartz	(CAS No) 14808-60-7	5 - 10	Acute Tox. 4 (Oral), H302 Carc. 1A, H350 STOT RE 1, H372
Calcium magnesium hydroxide (CaMg(OH)4)	(CAS No) 39445-23-3	3 - 7	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Calcium magnesium hydroxide oxide (CaMg(OH)2O)	(CAS No) 58398-71-3	3 - 7	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Magnesium oxide (MgO)	(CAS No) 1309-48-4	3 - 7	Not classified
Calcium hydroxide	(CAS No) 1305-62-0	1 - 5	Skin Corr. 1B, H314
Magnesium hydroxide	(CAS No) 1309-42-8	1 - 5	Not classified
Calcium sulfate	(CAS No) 7778-18-9	1 - 5	Not classified
Gypsum (Ca(SO4).2H2O)	(CAS No) 13397-24-5	1 - 5	Not classified
Limestone	(CAS No) 1317-65-3	1 - 5	Not classified
Calcium oxide	(CAS No) 1305-78-8	1 - 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

^{*} Exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

First-aid measures after ingestion

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

Symptoms/injuries after skin contact

: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.

Symptoms/injuries after eye contact

: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion

Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : Not available.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

06/10/2014 EN (English) 2/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

5.3. Advice for firefighters

Firefighting instructions

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

For containment

: Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Vacuum or sweep material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only outdoors or in a well-ventilated area. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Store locked up. Store in a well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total); 5 mg/m³ (resp)

Iron oxide (Fe2O3) (1309-37-1)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	10 mg/m3

Quartz (14808-60-7)	Quartz (14808-60-7)	
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	(30)/(%SiO2 + 2) mg/m³ TWA, (total) (250)/(%SiO2 + 5) mppcf TWA, (resp) (10)/(%SiO2 + 2) mg/m³ TWA, (resp)

Magnesium oxide (MgO) (1309-48-4)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³

Calcium hydroxide (1305-62-0)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total); 5 mg/m³ (resp)

Magnesium hydroxide (1309-42-8)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m3

06/10/2014 EN (English) 3/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Calcium sulfate (7778-18-9)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total); 5 mg/m³ (resp)

Gypsum (Ca(SO4).2H2O) (13397-24-5)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total); 5 mg/m³ (resp)

Limestone (1317-65-3)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total); 5 mg/m³ (resp)

Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³

8.2. **Exposure controls**

Explosive properties

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear suitable waterproof gloves.

Eye protection Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and

face protection (face shield).

Skin and body protection : Wear suitable waterproof protective clothing.

Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when

permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator

standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Other information Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink

where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Solid Appearance Powder. Colour Various. Odour Characteristic. Odour threshold No data available.

Relative evaporation rate (butylacetate=1) No data available. Melting point No data available. Freezing point No data available. Boiling point No data available. Flash point No data available. Self ignition temperature No data available. Decomposition temperature No data available. Flammability (solid, gas) Not flammable. Vapour pressure No data available. Relative vapour density at 20 °C No data available. Relative density No data available. Solubility No data available. Log Pow No data available. Log Kow No data available. Viscosity, kinematic No data available. Viscosity, dynamic No data available.

06/10/2014 EN (English) 4/7

: No data available.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Oxidising properties : No data available. Explosive limits : No data available.

9.2. Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Calcium oxide (1305-78-8)

Serious eye damage/irritation

Respiratory or skin sensitisation

LD50 oral rat

Carcinogenicity

Skin corrosion/irritation

Germ cell mutagenicity

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

Association Filhon Boson Ocat Ocaracatasta Otacon		
Amerimix Fiber Base Coat Concentrate Stucce		
LD50 oral rat	~1880 mg/kg, rat	
LD50 dermal rabbit	No data available.	
LC50 inhalation rat	No data available.	
Ashes, residues (68131-74-8)		
LD50 oral rat	> 2000 mg/kg	
Iron oxide (Fe2O3) (1309-37-1)		
LD50 oral rat	> 10000 mg/kg	
Quartz (14808-60-7)		
LD50 oral rat	500 mg/kg	
Magnesium oxide (MgO) (1309-48-4)		
LD50 oral rat	>5000 mg/kg	
Calcium hydroxide (1305-62-0)		
LD50 oral rat	7340 mg/kg	
Magnesium hydroxide (1309-42-8)		
LD50 oral rat	8500 mg/kg	
Calcium sulfate (7778-18-9)		
LD50 oral rat	> 3000 mg/kg	
Limestone (1317-65-3)		
LD50 oral rat	6450 mg/kg	

06/10/2014 EN (English) 5/7

Based on available data, the classification criteria are not met.

>2000 mg/kg

Causes skin irritation.

: May cause cancer.

Causes serious eye damage.

: May cause an allergic skin reaction.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Inon suide (Fe2O2) (4200 27.4)		
Iron oxide (Fe2O3) (1309-37-1)		
IARC group	3 - Not classifiable	
Quartz (14808-60-7)		
IARC group	1 - Carcinogenic to humans	
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens	
Reproductive toxicity	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)	
Aspiration hazard	: Based on available data, the classification criteria are not met.	
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.	
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.	
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2. Persistence and degradability

Amerimix Fiber Base Coat Concentrate Stucco	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

Amerimix Fiber Base Coat Concentrate Stucco	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Amerimix Fiber Base Coat Concentrate Stucco	
Ecology - soil	No data available.

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

06/10/2014 EN (English) 6/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Gypsum (Ca(SO4).2H2O) CAS No 13397-24-5

15.2. US State regulations

Amerimix Fiber Base Coat Concentrate Stucco	
State or local regulations	This product contains Crystalline Silica, Quartz and may also contain other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
	to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Indication of changes : None.

Date of issue : 06/10/2014

Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom

2012.

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention

was given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure

conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/10/2014 EN (English) 7/7