

SAFETY DATA SHEET

Issue Date 16-Jun-2015 Revision Date 16-Jun-2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name

AIR-BLOC LF LIQUID APPLIED WINDOW AND DOOR FLSH MEMBRANE

Other means of identification

Product Code HE022BWB Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation Causes serious eye irritation May cause respiratory irritation



Appearance viscous

Physical state liquid

Odor Slight

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Wash hands thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

IARC has classified occupational exposure to straight-run bitumen and their emissions during road paving as a carcinogen (category 2B - possibly carcinogenic to humans).

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Substance</u>

Chemical Name	CAS No	Weight-%	Trade Secret
Calcium Carbonate	1317-65-3	30 - 60	*
Silyl-terminated Polyether	Proprietary	10 - 30	*
Polyol Blend	Proprietary	5 - 10	*

Mica	12001-26-2	5 - 10	*
Non-phthalate plasticizer	Proprietary	5 - 10	*
Cyclosiloxane	Proprietary	1 - 5	*
Silica, quartz	14808-60-7	<0.1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

HE022BWB - AIR-BLOC LF LIQUID APPLIED WINDOW AND DOOR FLSH MEMBRANE

WINDOW AND DOOR FLSH MEMBRANE

Revision Date 16-Jun-2015

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 5 mg/m³ respirable fraction	
Mica 12001-26-2	TWA: 3 mg/m³ respirable fraction	(vacated) TWA: 3 mg/m³ respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica	IDLH: 1500 mg/m³ TWA: 3 mg/m³ containing <1% Quartz respirable dust
Silica, quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Slight

Information on basic physical and chemical properties

Physical state liquid **Appearance** viscous

Color blue Odor threshold No information available

Odor

Property Remarks • Method Values

6-11 Ha

Melting point / freezing point No information available Boiling point / boiling range > 100 °C / 212 °F Flash point 100 °C / > 212 °F

Evaporation rate

Flammability (solid, gas)

No information available Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Vapor pressure 0 kPa at 25C

Vapor density No information available

Relative density 1.56 Water solubility insoluble

Solubility in other solvents No information available Partition coefficient No information available Autoignition temperature No information available Decomposition temperature No information available Kinematic viscosity >50.000 cSt @ 25C Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

No information available Softening point Molecular weight No information available **VOC Content (%)** No information available Density No information available **Bulk density** No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation May cause irritation.

Eye contact Severely irritating to eyes.

Skin contact Irritating to skin.

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Polyol Blend	= 3750 mg/kg (Rat) > 2 g/kg (-	-
	Rat)		
Silica, quartz	= 500 mg/kg (Rat)	-	-
14808-60-7			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica, quartz	A2	Group 1	Known	X
14808-60-7				

Reproductive toxicity No information available.

STOT - single exposure Target Organs. Respiratory system.

STOT - repeated exposure Aspiration hazardNo information available.
No information available.

Numerical measures of toxicity - Product Information

 ATEmix (oral)
 8,000.00 mg/kg

 ATEmix (dermal)
 8,000.00 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-dust/mist)
 20.00 mg/kg

 ATEmix (inhalation-vapor)
 99,999.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

Bioaccumulative potential.

Other adverse effects No information available

Ozone Not applicable

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT Not regulated

Not regulated TDG

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** No Fire hazard No Sudden release of pressure hazard No

Reactive Hazard

No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause cancer.

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0 Physical and Chemical

Properties -

Revision Date 16-Jun-2015

Health hazards 1 Flammability 1 Physical hazards 0 Personal protection X

Issue Date16-Jun-2015Revision Date16-Jun-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet