Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name SOUDASEAL SL

Manufacturer Information

SOUDAL ACCUMETRIC 350 Ring Road, Elizabethtown, KY 42701 Phone: 1-877-873-8739 Emergency Phone #: +1 800 424 9300 E-mail: info@soudalusa.com

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Serious Eye Damage/Eye Irritation - Category 2A Skin Sensitization - Category 1

GHS Label Elements

Symbol(s)



Signal Word Warning

Hazard Statement(s)

Causes serious eye irritation May cause allergic skin reaction

Precautionary Statement(s)

Prevention

Wear eye protection/face protection Avoid breathing dust/fume/gas/mist/vapours/spray Wash thoroughly after handling Contaminated work clothing must not be allowed out of the workplace Wear protective gloves

Response

Material Name: SOUDASEAL SL

SDS ID: SD-007

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse Specific treatment (see label)

Storage

None needed according to classification criteria

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

CAS	Component Name	Percent
1317-65-3	Ground Limestone	50 - 55
NA1	Silyl Terminated Polyether	20-25
26761-40-0	Diisodecyl phthalate	13
13463-67-7	Titanium dioxide(inbound in mixture)	5-10
64742-46-7	Distillates (petroleum), hydrotreated middle	1-5
1760-24-3	Aminoethyl aminopropyl trimethoxy silane	<1
22673-19-4	Dibutyltin Diacetyldiacetonate	<1
2768-02-7	Vinyltrimethoxysilane	<1
52829-07-9	Bis(2,2,6.6-tetramethyl-4-piperidyl)- sebacate	<1
3864-99-1	Phenol, 2-(5-chloro-2H-benzotriazol-2- yl)-4,6-bis(1,1-dimethylethyl)-	<1

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Material Name: SOUDASEAL SL

SDS ID: SD-007

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Specific treatment (see label).

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

If a large amount is swallowed, get medical attention.

Indication of any immediate medical attention and special treatment needed Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

Causes serious eye irritation.

Delayed

May cause allergic skin reaction.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical None known.

Hazardous Combustion Products Oxides of carbon, carbon monoxide, oxides of calcium

Special Protective Equipment and Precautions for Firefighters

Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Dike for later disposal.

Fire Fighting Measures

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid contact with skin and eyes. Wash contaminated clothing before reuse.

Methods and Materials for Containment and Cleaning Up

Material Name: SOUDASEAL SL

SDS ID: SD-007

Keep unnecessary people away, isolate hazard area and deny entry. Only personnel trained for the hazards of this material should perform clean up and disposal.

Environmental Precautions

Collect spilled material using mechanical equipment. Keep out of water supplies and sewers.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Provide adequate ventilation. Wash thoroughly after handling. Wear protective gloves/clothing and eye/face protection.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in a cool dry place. Keep away from incompatible materials.

Incompatible Materials

oxidizing materials, bases, combustible materials, strong acids, strong bases

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits	
---------------------------	--

Ground Limestone	1317-65-3
NIOSH:	10 mg/m3TWAtotal dust; 5 mg/m3TWArespirable dust
OSHA (US):	15 mg/m3TWAtotal dust; 5 mg/m3TWArespirable fraction
Mexico:	10 mg/m3TWA LMPE-PPT
	20 mg/m3STEL [LMPE-CT]
Titanium dioxide(inbound in mixture)	13463-67-7
ACGIH:	10 mg/m3 TWA
NIOSH:	5000 mg/m3IDLH
OSHA (US):	15 mg/m3TWAtotal dust
Mexico:	10 mg/m3TWA LMPE-PPT as Ti
	20 mg/m3STEL [LMPE-CT] as Ti

Biological limit value

There are no biological limit values for any of this product's components.

Material Name: SOUDASEAL SL

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Not available	Physical State	Unknown
Odor	typical	Color	various colors
Odor Threshold	Not available	рН	Not available
Melting Point	Not available	Boiling Point	Not available
Freezing point	Not available	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	200 °C
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	Insoluble	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Bulk Density	Not available	Density	1.5
Log KOW	Not available	Physical Form	paste
VOC	10 gm/liter	Volatility	Not available
OSHA Flammability Class	Not available		

Material Name: SOUDASEAL SL

Section 10 - STABILITY AND REACTIVITY

Reactivity

No hazard expected.

Chemical Stability Stable under normal conditions of use.

Possibility of Hazardous Reactions No hazard expected.

Conditions to Avoid

Avoid contact with incompatible materials.

Incompatible Materials oxidizing materials, bases, combustible materials, strong acids, strong bases

Hazardous decomposition products

oxides of carbon, carbon monoxide, oxides of calcium

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

May cause allergic skin reaction.

Eye Contact

Causes serious eye irritation.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published: Diisodecyl phthalate (26761-40-0) Oral LD50Rat 64 g/kg Dermal LD50Rabbit >3160 mg/kg Inhalation LC50Rat >12.54 mg/L 4 h Titanium dioxide(inbound in mixture) (13463-67-7) Oral LD50Rat >10000 mg/kg Distillates (petroleum), hydrotreated middle (64742-46-7) Oral LD50Rat 7400 mg/kg Dermal LD50Rabbit >2000 mg/kg Inhalation LC50Rat 4.6 mg/L 4 h Bis(2,2,6.6-tetramethyl-4-piperidyl)-sebacate (52829-07-9) Inhalation LC50Rat 500 mg/m3 4 h

Material Name: SOUDASEAL SL

Immediate Effects

Causes serious eye irritation.

Delayed Effects May cause allergic skin reaction.

Irritation/Corrosivity Data

Causes serious eye irritation.

Respiratory Sensitization No data available.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

Diisodecyl phthalate	26761-40-0
DFG:	Category 3B (could be carcinogenic for man)
Titanium dioxide(inbound in mixture)	13463-67-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 93 [2010]; Monograph 47 [1989](Group 2B (possibly carcinogenic to humans))
DFG:	Category 3A (could be carcinogenic for man, inhalable fraction with the exception of ultra small particles)
OSHA:	Present

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure No information on significant adverse effects.

Specific Target Organ Toxicity - Repeated Exposure No information on significant adverse effects.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

eye disorders, skin disorders

Section 12 - ECOLOGICAL INFORMATION

Material Name: SOUDASEAL SL

Diisodecyl phthalate	26761-40-0					
Fish:	LC50 96 h Lepomis macrochirus >0.55 mg/L [static]; LC50 96 h Pimephales promelas >1 mg/L [flow-through]					
Algae:	EC50 72 h Desmodesmus subspicatus >500 mg/L IUCLID; EC50 96 h Pseudokirchneriella subcapitata >0.8 mg/L [static] EPA					
Invertebrate:	EC50 48 h Daphnia magna >0.02 mg/L [static] EPA					
Distillates (petroleum), hydrotreated middle	64742-46-7					
Fish:	LC50 96 h Pimephales promelas 35 mg/L [flow-through]; LC50 96 h Pimephales promelas >10000 mg/L [static]					

Component Analysis - Aquatic Toxicity

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not Regulated

TDG Information:

UN#: Not Regulated

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	
-----------	-----	----	----	----	----	----	--

Material Name: SOUDASEAL SL

SDS ID: SD-007

Ground Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Titanium dioxide(inbound in mixture)	13463-67-7	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Diisodecyl phthalate	26761-40-0								
Repro/Dev. Tox	developmental toxicity, initial date 4/20/07								
Titanium dioxide(inbound in mixture)	13463-67-7								
Carc:	carcinogen, initial date 9/2/11 (airborne, unbound particles of respirable size)								

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

WHMIS Classification D2B

Component Analysis - Inventory

Ground Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Diisodecyl phthalate (26761-40-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Titanium dioxide(inbound in mixture) (13463-67-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Distillates (petroleum), hydrotreated middle (64742-46-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	
----	----	----	----	----	--------------	--------------	-------------------	--------------	----	----	----	--

Material Name: SOUDASEAL SL

SDS ID: SD-007

	1										
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Ami	noethy	l amin	oprop	yl trin	ethoxy silar	ne (1760-24	-3)				
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	No
Dibu	ıtyltin l	Diacet	yldiac	etonat	e (22673-19	-4)					
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	МХ
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No
Viny	ltrimet	hoxys	ilane ((2768-	02-7)						
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	МХ
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No
Bis(2	2,2,6.6-	-tetram	nethyl	-4-pip	eridyl)-sebad	cate (52829	-07-9)				
					JP -	JP -	KR -	KR -			
US	CA	EU	AU	PH	ENCS	ISHL	KK - KECI/KECL	TCCA	CN	NZ	MX
US Yes	CA DSL	EU EIN	AU Yes	PH Yes		1.			CN Yes	NZ Yes	MX Yes
Yes	DSL	EIN	Yes	Yes	ENCS Yes	ISHL No	KECI/KECL Yes	TCCA No			
Yes	DSL	EIN	Yes	Yes	ENCS Yes	ISHL No	KECI/KECL	TCCA No			

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 3 Fire: 1 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 3 Fire: 1 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Key / Legend

Material Name: SOUDASEAL SL

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation: DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database: MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental, consequential, or other such damages resulting from its use or misuse.

Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.