

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 04/14/2015 Revision date: 04/14/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Amerimix Portland Cement

Product code : 62150005 - 94lb

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Various

1.3. Details of the supplier of the safety data sheet

Oldcastle Architectural Inc. 900 Ashwood Parkway Suite 600 Atlanta, GA 30338 - USA

T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irritation 2

Serious Eye Damage 1

Skin Sensitization 1

Carcinogenicity 1A

Specific Target Organ Toxicity - Single Exposure 3 Specific Target Organ Toxicity - Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS05

GHS07



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or

repeated exposure.

Precautionary statements (GHS-US)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS US)

50 % of the mixture consists of ingredient(s) of unknown acute toxicity.

04/14/2015 EN (English) Page 1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Cement, portland, chemicals	(CAS No) 65997-15-1	50 - 100	Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1 STOT SE 3
Limestone	(CAS No) 1317-65-3	≤50	Not classified
Calcium sulfate	(CAS No) 7778-18-9	≤7	Not classified
Quartz	(CAS No) 14808-60-7	≤3	Carc. 1A STOT RE 1

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

First-aid measures after ingestion

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

Symptoms/injuries after skin contact

Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Symptoms/injuries after eye contact

: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion

: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Treat for surrounding material.

Unsuitable extinguishing media

: Not available.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Protection during firefighting

Troducts of combustion may include, and are not limited to: oxides of carbon.

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

For containment

: Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter

Methods for cleaning up

: Vacuum or sweep material and place in a disposal container. Provide ventilation.

waterways. Use appropriate Personal Protective Equipment (PPE).

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

04/14/2015 EN (English) 2/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals (65997-15-1)		
ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) 50 mppcf (<1% Crystalline silica)

Limestone (1317-65-3)		
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (total dust)
OSHA	OSHA PEL (TWA) (mg/m³) 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)	

Calcium sulfate (7778-18-9)		
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m³)	$(30)/(\%SiO_2 + 2) \text{ mg/m}^3 \text{ (total dust)}$ $(250)/(\%SiO_2 + 5) \text{ mppcf (respirable fraction)}$ $(10)/(\%SiO_2 + 2) \text{ mg/m}^3 \text{ (respirable fraction)}$

8.2. Exposure controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection

: Wear suitable waterproof gloves.

Eye protection

: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles)

and face protection (face shield).

Skin and body protection

: Wear suitable waterproof protective clothing.

Respiratory protection

: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator

standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Environmental exposure controls

: Maintain levels below Community environmental protection thresholds.

Other information

: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Powder

04/14/2015 EN (English) 3/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Colour : Various Odour Characteristic Odour threshold : No data available

Hq : 12 - 13

No data available Melting point No data available Freezing point Boiling point : No data available Flash point No data available Relative evaporation rate (butylacetate=1) : No data available : Not flammable Flammability (solid, gas) : No data available **Explosive limits** Explosive properties : No data available Oxidising properties : No data available Vapour pressure : No data available : 2.87 - 3.00 Relative density

Relative vapour density at 20 °C Solubility : Water: slight (0.1 to 1.0%)

Partition coefficient: n-octanol/water No data available Log Kow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available : No data available Viscosity Viscosity, kinematic No data available Viscosity, dynamic : No data available

Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

No data available

SECTION 10: Stability and reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

10.2. **Chemical stability**

Stable under normal storage conditions. Keep dry in storage.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Incompatible materials. Moisture.

Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

Hazardous decomposition products

May include, and are not limited to: oxides of carbon, calcium hydroxide.

SECTION 11: Toxicological information

Information on toxicological effects 11.1.

Acute toxicity : Not classified.

Amerimix Portland Cement	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	No data available.
LC50 inhalation rat	No data available.

Limestone (1317-65-3)

LD50 oral rat	6450 ma/ka

04/14/2015 EN (English) 4/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Calcium sulfate (7778-18-9)	
LD50 oral rat	> 3000 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: May cause cancer.
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2. Persistence and degradability

Amerimix Portland Cement	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

Amerimix Portland Cement	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Amerimix Portland Cement	
Ecology - soil	No data available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

04/14/2015 EN (English) 5/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Not regulated for transport.

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

Amerimix Portland Cement

04/14/2015

State or local regulations

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Date of issue : 04/14/2015 Other information : None.

NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was


iiven.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

EN (English)

and are not reactive with water.



6/6

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.