

# SAFETY DATA SHEET



Issue Date: July 31, 2014

Revision Date: July 31, 2014

Version: 2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name(s): SpeedPatch

### Other Means of Identification

SDS #: F2000F

Recommended Use: Cement Patching

Restrictions on Use: No Data

### Supplier of the Safety Data Sheet including Address:

ChemMasters Inc.  
300 Edwards Street  
Madison, OH 44057

### Telephone Numbers

Company Phone Number

Phone: 800-486-7866, 440-428-2105

Fax: 440-428-7091

Emergency Telephone: ChemTrec 800-424-9300 (United States & Canada), International Call: 1-703-527-3887

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### OSHA Hazards:

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful if inhaled. Suspected of causing cancer by inhalation of respirable crystalline silica. Causes damage to Lungs through prolonged or repeated exposure by inhalation.

Target Organs: Lungs

#### GHS Classification:

Acute Toxicity Oral – Category 4

Carcinogenicity – Category 2

Eye damage/eye irritation – Category 1

Skin sensitization – Category 1

Skin irritation – Category 1

Specific target organ toxicity – repeated exposure – Category 2, Respiratory System

Label Elements, including precautionary statements

Pictograms:



Signal Word: DANGER

SpeedPatch, Page 1 / 7

**Hazard Statements:**

- H302 Harmful if swallowed
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

**Precautionary Statement(s)****Prevention:**

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash hands and skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P310 Immediately call a POISON CENTER/doctor.
- P303+P313+P310 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with plenty of water or shower. Immediately call a POISON CENTER/doctor.
- P363 Wash contaminated clothing before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice or attention.
- P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P314 Repeated Exposure: Get medical advice/attention if you feel unwell.

**Storage:**

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Disposal:**

- P501 Dispose of contents/container in accordance with local/regional/national regulations.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Component**

Crystalline Silica in the form of Quartz	CAS#: 14808-60-7	50-55%
Cement Mixture	CAS#: 65997-15-1, 960375-09-1, 7778-18-9, 65997-16-2	40-45%
Calcium Magnesium Hydroxide	CAS#: 39445-23-3	1-5 %
Titanium Dioxide	CAS#: 13463-67-7	<0.5 %
Lithium Carbonate	CAS#: 554-13-2	<0.5%

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels.

## 4. FIRST AID MEASURES

### **First Aid Measures**

General Advice: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

**Inhalation:** If breathed in, move person into fresh air and keep comfortable for breathing. Consult a physician.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician.

**Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

**Skin Contact:** Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

## 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Material is Non-combustible. Use Water spray, alcohol-resistant foam, dry chemical, or carbon dioxide for surrounding fire.

### **Specific Hazards Arising from the Chemical**

Avoid breathing dust. Wet cement is caustic.

### **Hazardous Combustion Products**

Calcium Oxide, Sulfur Dioxide

### **Protective Equipment and Precautions for Firefighters**

Wear self-contained breathing apparatus and full protective gear for firefighting.

**Further Information:** See Section 7 for safe handling and storage.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal Precautions, Protective Equipment and Emergency Procedures**

Avoid actions that cause the material to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment during any cleanup and response activities.

### **Environmental Precautions**

Do not wash cement down sewage and drainage systems or into bodies of water.

### **Methods and Material for Containment and Cleaning Up**

Place spilled material into a container. Scrape wet material and place in container. Allow material to dry or solidify before disposal. Dispose of cement according to Federal, State, Provincial and Local regulations.

## 7. HANDLING AND STORAGE

### **Precautions for Safe Handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

### **Conditions for Safe Storage, Including any Incompatibilities**

**General information:** Keep bagged material dry until used. Stack bagged material in a secure manner to prevent falling. Bagged material is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures.

**Incompatibilities:** Water will cause product to solidify.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Component Exposure Limits

Cement CAS#: 65997-15-1 OSHA 15 mg/m<sup>3</sup> T (Total) / 5 mg/m<sup>3</sup> R (Respirable)

Silica, Quartz CAS#: 14808-60-7 OSHA TWA 10 mg/m<sup>3</sup>, ACGIH TWA 0.025 mg/m<sup>3</sup>

Titanium Dioxide CAS#: 13463-67-7 OSHA 15 mg/m<sup>3</sup>, 8 hr. TWA Total Dust

#### Appropriate Engineering Controls

Local Ventilation: Recommended

General Ventilation: Recommended

#### Individual Protection Measures, such as Personal Protective Equipment

**Eye/Face Protection:** Use proper protection – Safety Glasses as a minimum

**Skin and Body Protection:** Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

**Respiratory Protection:** Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

#### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

#### Physical State

**Appearance:** Solid Powder

**Color:** Gray

**Odor:** Mild

**Odor threshold:** No Data

<u>Property</u>	<u>Value</u>	<u>Remarks – Method</u>
Vapor Pressure	Not Available	
Vapor Density	Not Available	
Relative Density	Not Available	
pH (In Water)	12-13	
Melting/Freezing Point	Not Relevant	
Solubility	Not Available	
Evaporation Rate	Not Available	
Flash Point	Not Relevant	
Flammability Limits	Not Available	
Flammability (Solid, gas)	Not Relevant	
Auto Ignition Temperature	Not Available	
Initial Boiling Point/Boiling Range	Not Available	
Decomposition Temperature	Not Available	
Viscosity	Not Available	
Specific Gravity	Not Available	

## 10. STABILITY AND REACTIVITY

### Chemical Stability:

Stable.

### Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

### Conditions to Avoid:

Keep dry until use. Avoid contact with incompatible materials.

### Incompatible Materials:

Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

### Hazardous Decomposition Products:

None known

## 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact, Ingestion

### Symptoms of Exposure:

Inhalation: May cause respiratory irritation

Skin: Causes severe skin burns. May cause allergic skin reaction.

Eyes: Causes serious eye damage

Ingestion: Irritation of the digestive system may occur if large amounts are swallowed.

### Numerical measures of toxicity:

Acute Toxicity Value: Silica-LD50 oral rat 22,500 mg/kg

### Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

#### **Dermatitis:**

**Irritant Dermatitis** is caused by physical properties of cement including alkalinity and abrasion. **Allergic Dermatitis** is caused by sensitization to hexavalent chromium (Chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

#### **Carcinogenicity:**

**IARC:** 1-Group 1: Carcinogenic to humans (Quartz); Group 2B Possibly Carcinogenic to humans (Titanium Dioxide).

**ACGIH:** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**NTP:** Carcinogenic to humans (Quartz)

**OSHA:** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Specific target organ toxicity:** Single exposure – No data available.

**Specific target organ toxicity:** Repeated exposure – Category 2, Respiratory System.

**Silicosis:** Silicosis is caused by the inhalation and retention of respirable crystalline silica dust.

**Simple Chronic Silicosis** - results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).

**Accelerated silicosis** – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.

**Acute silicosis** – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

**Pre-Existing Conditions:** Cement dust is irritating to the nose, throat and respiratory tract causing coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

## 12. ECOLOGICAL INFORMATION

**Eco toxicity:** Not expected to be hazardous to the environment.

**Persistence and Degradability:** No Data Available

**Bioaccumulation:** No Data Available

**Mobility:** No Data Available

**Other Adverse Effects:** No Data Available

## 13. DISPOSAL CONSIDERATIONS

### Waste Treatment Methods

**Disposal of Wastes:** This product is not expected to be a hazardous waste under RCRA. Place spilled material into a container. Scrape wet material and place in container. Allow material to dry or solidify before disposal. Dispose of according to Federal, State, Provincial and Local regulations.

**Contaminated Packaging:** Dispose of as unused material.

## 14. TRANSPORT INFORMATION

**DOT:** Not a Dangerous Good

**IATA:** Not a Dangerous Good

**IMDG:** Not a Dangerous Good

**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA:** All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

### US Federal Regulations

**SARA 302:** None Known

**SARA 311/312 Hazard Categories:** Acute Health Hazard, Chronic Health Hazard

**SARA 313 Hazard Categories:** None Known

**CWA (Clean Water Act):** None Known

**Supplemental State Compliance Information**

California:

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

- Quartz CAS#:14808-60-7
- Hexavalent Chromium Compounds
- Titanium Dioxide CAS# 13463-67-7
- Lithium Carbonate CAS# 554-13-2

State Right To Know:

<u>Component Name</u>	<u>State</u>
Quartz, CAS#: 14808-60-7	New Jersey, Pennsylvania, Massachusetts
Lithium Carbonate, CAS#: 554-13-2	New Jersey, Massachusetts
Titanium Dioxide, CAS#: 13463-67-7	New Jersey, Pennsylvania, Massachusetts

Michigan Critical Materials Register

Lithium Compounds (Lithium Carbonate) CAS#: 554-13-2

**U.S. EPA Label Information:** No Data

**Canada**

WHMIS Classification: Class D2B (Toxic) & Class E (Corrosive)

Symbol: Stylized T, Corrosive



**16. OTHER INFORMATION**

**HMIS Classification:**

- Health hazard:** 2
- Flammability:** 0
- Physical Hazards:** 0

**NFPA Rating:**

- Health hazard:** 2
- Fire:** 0
- Reactivity Hazard:** 0

**Issuance Date: July 31, 2014**

**Revision Date: July 31, 2014**

**Revision Note: GHS Format**

**Date of Previous Version: February 7, 2012**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**